

539.00 EUR
incl. 19% VAT, plus [shipping](#)



Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with 10-points Multi Capacitive Touch/Anti-Reflection Protection Glass type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

- 8.0" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Enclosed in robust aluminum casings
- A true Flat, easy-to-clean front surface with edge-to-edge design
- USB3.0 Support Lock Device
- Front IP65 for protection against water and dust
- 12V DC-input Support, with EOS, OVP design

Display	– IP65, NEMA 4 rugged protection, metal front bezel – 8.0" With LED Backlight – 400 nits – 16.7M display color – 1024 x 768 @60Hz resolution – 160°/160° viewing angle (H/V) – 0.158 x 0.158mm pixel pitch – 4:3 aspect ratio – 700:1 contrast ratio – 30ms response time
Touch Screen	– Projected capacitive type – 163.05 x 122.54mm ±0.2mm active range – Transparency ■ 85% – Operating force ■ 50g – Surface Hardness ■ 6H (JIS-5400) – Glass haze value■ 3%
Case	– Aluminum panel – Iron case – Silver + white color – Spray paint coating requirement
Main System	– Intel® Apollo Lake N3350 1.1GHz/DC processor – 1* DDR3L SO-DIMM (Max 8GB)) – 128MB SPI Flash ROM – Watchdog Timer 256 levels, 0~255 sec. – OS Support Windows 10 / Linux
Storage	– 1* M.2 Socket (2242 size)
Expansion	– 1* Mini PCIe for WIFI or 3G/4G
I/O Connector	– 2* USB3.0 – 1* RS232/422/485 + 1* RS232 – 1* HDMI – 1* Realtek® RTL8111H GbE – 1* Locking Jack 12V DC input – 1* SIM card slot – 1* Power button
Power Input	– AC version: 100~240V AC-DC 60W power adapter or – DC version: 12VDC with over current protection fuse
Power Consumption	– 13W
Dimensions	– 199.05 * 158.54 * 57.70mm
Compliance	– CE, FCC, IP65(Front)-Option
Safety	– Shock: 11ms duration – Vibration: 5~500Hz/1 Grms
Temperature	– Operating: -10°C ~ 60°C – Storage: -20°C ~ 70°C
Warranty	– 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty)